



MS[®]SUF Hollow Fiber UF Membrane

MS-SUF-4040

MEMBRANE DESCRIPTIONS

Membrane Material	Modified PES
Membrane Surface Areas (m ² /ft ²)	8/86.11
MWCO (Dal)	100,000
ID/OD (mm/inch)	0.7/1.3 (0.027/0.051)

OPERATION CONDITIONS

Max Feed Pressure (MPa/psi)	0.25/36.26
Max Flux (L/H)	1,200
Max TMP (MPa/psi)	0.15/21.75
Temperature Range (°C/°F)	5-40/41-104
pH Range	2-10

CLEANING CONDITIONS

Max Active Chlorine (ppm)	500
pH Range	2-11
Max Backwash Pressure (MPa/psi)	0.2/29.01
Backwash Flux (L/H)	600

www.membrane-solutions.com

USA

Phone: 1-214-775-2940

Address: JP Morgan International Plaza
Suite 650, 14241 Dallas Parkway,
Dallas, TX, US

China

Toll free: 400-620-1660


Fax: 0086-21-51687551

Address: 2202, No.1759 North Zhongshan
Road, Shanghai

MS[®]SUF Hollow Fiber UF Membrane

MS-SUF-4040

MEMBRANE MODULE DESCRIPTIONS



L1 (mm/inch)	1,150/45.27
L2 (mm/inch)	1,020/40.16
D (mm/inch)	90/3.54
A (mm/inch)	110/4.33
Connector	DN20/DN25
Housing Material	UPVC
Module Plate Material	UPVC
Seal Gum Material	Epoxy resin

www.membrane-solutions.com

USA

Phone: 1-214-775-2940

Address: JP Morgan International Plaza
Suite 650, 14241 Dallas Parkway,
Dallas, TX, US

China

Toll free: 400-620-1660

Fax: 0086-21-51687551

Address: 2202, No.1759 North Zhongshan
Road, Shanghai